



F - DUO Series & MOPA																					
MODEL		PULSED & PULSED UHS										MOPA									
POWER		10W		20W		30W		50W		100W		20W		50W							
WAVELENGTH		1.062 μm																			
FREQUENCY		25-100kh ²										φ-1000kh ²									
PULSE WIDTH		100ns										8 selectable 4-200ns									
LASER SYSTEM		F - 10 PULSED & PULSED UHS		F - 20 PULSED & PULSED UHS		F - 30 PULSED & PULSED UHS		F - 50 PULSED & PULSED UHS		F - 100 PULSED & PULSED UHS		F - 20 MOPA		F - 50 MOPA							
MAINS SUPPLY		100V - 240V 50 / 60 Hz (1 Phase + N) 300 VA		100V - 240V 50 / 60 Hz (1 Phase + N) 350 VA		100V - 240V 50 / 60 Hz (1 Phase + N) 400 VA		100V - 240V 50 / 60 Hz (1 Phase + N) 600 VA		100V - 240V 50 / 60 Hz (1 Phase + N) 750 VA		100V - 240V 50 / 60 Hz (1 Phase + N) 350 VA		100V - 240V 50 / 60 Hz (1 Phase + N) 600 VA							
DIMENSIONS		Head		108x106.5x469 mm						115x98x463 mm						108x106.5x469 mm		115x98x463 mm			
		Rack		464x177x550 mm																	
WEIGHT		Net weight: 23Kg - Gross Weight: 27Kg										Net weight: 23Kg - Gross Weight: 27Kg									
SYSTEM		Optical isolator and collimator of the laser source, galvanometric scanners built into the marking head. Control and power electronics, drivers of the scanners, CPU, power supplies and laser source built into the control rack.																			
FOCAL SPECIFIC.		TECHNOLOGY		PULSED						PULSED UHS						MOPA					
		MA (mm)	WD (mm)	FL (mm)	BD (μm)	PD (KW/cm ²)	PD (KW/cm ²)	PD (KW/cm ²)	PD (KW/cm ²)	PD (KW/cm ²)	BD (μm)	PD (KW/cm ²)	PD (KW/cm ²)	PD (KW/cm ²)	PD (KW/cm ²)	BD (μm)	PD (KW/cm ²)	PD (KW/cm ²)			
		55x55	141	100	16	9709	19417	29126	48542	97085	27	3482	6964	10446	17409	34819	16	19417	48542		
		100x100	205	163	26	3654	7308	10962	18270	36540	44	1327	2653	3980	6634	13267	26	7308	18270		
		168x168	347	254	41	1505	3009	4514	7524	15045	69	540	1079	1619	2698	5397	41	3009	7524		
		212x212	458	346	56	811	1622	2433	4054	8110	94	291	582	873	1454	2908	56	1622	4054		
		242x242	554	420	68	551	1101	1652	2752	5505	-	-	-	-	-	-	68	1101	2752		
		560x560	888,5	815	132	146	292	438	731	1460	-	-	-	-	-	-	132	292	731		
		LEGEND: WD:Working Distance FL:Focal Length MA:Marking Area BD: Spot Beam Diameter PD:Power Density																			
		IMPORTANT NOTE: Working Distance [WD]: The distance between the laser system base and the surface to be marked. Focal Length [FL]: The distance between the center of the lens and the surface to be marked. Approximate values: These values are an approximation, and they are different for each laser system, due to the different optical paths.																			
		SOFTWARE: ScanLinux (Standard). Crystal Font (Standard). Internal Barcode. Marca Lite Software.																			
		USER INTERFACE: Touch Screen. Hand Held Terminal. PC.																			
		CONTROLLED BY: Hand Held Terminal with ScanLinux software. Touch Screen with ScanLinux software. Full Graphics Interface: includes Marca™ software, dongle and Ethernet cable [TCP / IP]. Marca Lite Software: includes Marca™ software, dongle and Ethernet cable [TCP / IP].																			
		ACCESSORIES: Handheld Terminal-Touch Screen Terminal - Beam pointer - Encoder Kit - Photocell Kit - Alarm Kit - Fume Extractor - Mounting support - Mounting Bracket U-ARM - Marking paper - Protection goggles - Air Cooling Kit																			
		ENVIRONMENTAL CONDITIONS: +15°C (59°F) at 40°C (104°F) external temperature with 50% Duty Cycle or 36°C(100°F) external temperature with 100% Duty Cycle. Humidity between 10% and 95%, without condensation. No vibrations.																			

* approximate data that may have small variations in reality



Version MAY 2018

F DUO Series

INDUSTRIAL FIBER LASER

High precision 2D and 3D marking on metals



Coding, tracing and marking solutions worldwide



T. 93 873 87 98
macsa@macsa.com
www.macsa.com

Macsa ID Headquarter
P.I. Pla de Santa Anna
08272 Sant Fruitós de
Bages (Barcelona)
Tel: +34 938 738 798
Spain

Macsa ID UK
13d Old Bridge Way
Shefford
Bedfordshire
SG175HQ
+44 (0)1462 816091
UK

Macsa ID Portugal
Rua Eng. Frederico Ulrich n. 2650.
4470 - 605 Moreira Maia
Tel: +351 229962204
Portugal

Macsa ID Malaysia
E-8-03, The Gamuda Biz Suites
No.12, Jalan Anggerik Vanilla 31/99,
Kota Kemuning,
40460 Shah Alam
Selangor
Malaysia

Macsa Coding Technology (shenzhen) Co. Ltd
East side of 2/F, 7 Building
Lijincheng Technology Industry Park
Jihua Road
Longhua Street, Longhua District
518100 Shenzhen
Tel: +86 0755-23611591
China

F DUO Series by **MACSA**
Powerful. Reliable. Precise.

INDUSTRIAL FIBER LASER

F DUO Series

A family of powerful and reliable industrial fibre lasers.

F DUO lasers are **designed for high-speed on-line integration and for use in standalone workstations.**

They are ideal for demanding metal marking applications, but are also effective with other materials such as plastics and composite materials.

F DUO lasers are long life, low maintenance lasers with very low cost of ownership.

The F DUO pulsed fiber laser product range has been extended to include MOPA lasers.



F MOPA

For high precision marking

MOPA technology allows the shape and duration of the waveform to be controlled and selected by the user in order to optimize the conditions for high precision marking and micro machining applications.

- Shorter pulse widths are ideal for marking delicate substrates such as plastics or thin materials. An extended frequency range enables higher repetition rates with shorter pulse widths to be used which leads to higher productivity.
- Longer pulse widths are ideal for deep engraving and other bulk material removal applications.

The key to high precision marking applications is precise thermal management and with 8 selectable and programmable pulse widths. F MOPA laser is the perfect tool for those demanding, high value add applications.



Macsa lasers are very easy to use thanks to our powerful proprietary marking software.

Marca makes it simple to code and mark precisely and consistently. A userfriendly software to create text, 1D and 2D codes, 3D graphics, graphical files, etc...



The modular software to control, manage and optimize the production line.



Solution of monitoring services, predictive maintenance, remote assistance and production support

3D marking

2D marks can be mapped to regular 3D geometries such as cylinders, spheres and cones. Additionally irregular geometries can be loaded as 3D CAD files in to Marca software enabling 2D marks to be mapped to irregular 3D surfaces. The Macsa 3D scan head greatly simplifies the mechanical handling of 3D geometries and can eliminate the need for rotary and robotic handling devices. This can significantly increase productivity.

DUO by Macsa

Dual Processor Technology Lasers by Macsa allows high precision marks to be produced even with variable data with no loss of performance. This technology dedicates one processor to data processing and the other to controlling the laser.

3-D Print Head transform your 2D laser to 3D

