



for Micro Four Thirds System

New Dilll Series 14-150mm



A compact all-in-one™ lens that combines extreme versatility and exceptional image quality.

14-150mm F/3.5-5.8 Dill

For Micro Four Thirds mirrorless interchangeable-lens cameras*

Model C001 Available in Black and Silver finish

This Di III lens is digitally optimized for mirrorless interchangeable-lens cameras. It comes with matching flower-shaped lens hood.

Micro Four Thirds™ and the Micro Four Thirds logo marks are trademarks or registered trademarks of Olympus Imaging Corporation, in Japan, the United States, the European Union, and other countries. The company names and product names in this document are the trademarks or registered trademarks of their respective owners.

^{* &}quot;Mirrorless interchangeable-lens cameras" are also known as "Compact System Cameras".

This product conforms to the "Micro Four Thirds System Standard" established by Olympus Imaging Corporation and Panasonic Corporation.



Introducing the first Micro Four Thirds lens from Tamron: High-power all-in-one™ zoom in a choice of two colors.



Developed by Olympus Imaging and Panasonic, Micro Four Thirds is a new system standard for compact mirrorless interchangeable-lens cameras that enables users to capture high-quality images using smaller, lighter equipment. Now, Tamron has expanded the possibilities of the Micro Four Thirds system with an innovative 14-150mm zoom lens (equivalent to 28-300mm in the 35mm and full-frame formats). This 10.7x zoom weighs only 285g (10.1oz) and

has a compact form factor that accepts a 52mm diameter filter. Available in a sophisticated black or silver finish, this unique lens makes it easy to compose and capture sharp pictures over a very wide range of shooting conditions. It's ideal for travel, family, and creative photography.



* Cameras are shown with Tamron lenses attached

The essence of Tamron technology in a compact, all-in-one™ zoom that minimizes aberrations and maximizes image quality

The optical design of this lens includes one LD (Low Dispersion) glass element, two AD (Anomalous Dispersion) glass elements, two Molded-Glass Aspherical elements, and one Hybrid Aspherical element. This formula reduces aberrations to a bare minimum to achieve exceptional class-leading image quality. The 14-150mm zoom is the fruit of Tamron's 20+ years of experience in designing and manufacturing world-class all-in-one™ zoom lenses.

C001 Angles of View





14mm ▶ 28mm (F)



A Stepping Motor for quick, quiet auto-focusing

The stepping motor's actuator allows precise control of angular rotation, and since it drives the focusing mechanism directly without any intermediary reduction gear, it is also exceptionally quiet. These features also give the lens a seamless, fluid auto-focusing action when shooting video.

<Stepping Motor Schematic Diagram>



For more information about the C001, please visit the C001 Special Website

Www.tamron.co.jp/en/lineup/c001/

14-150mm F/3.5-5.8 Di III for Micro Four Thirds mirrorless interchangeable-lens cameras. Model: C001 Color: Black / Silver Filter Size

Length*2

Diameter

Weight

Model

Focal Length 14-150mm (equivalent to 28-300mm in the 35mm / full-frame format)

Maximum Aperture F/3.5-5.8 Angle of View (diagonal) 75°22'~ 8°15'*1

Lens Construction 17 elements in 13 groups

Minimum Focus Distance 0.5m (19.7in)

Max. Magnification Ratio 1:3.8 (at f = 150mm, MFD 0.5m)

Specifications, appearance, functionality, etc. may be changed without prior notice *1: Case of aspect ratio "4:3" *2: Length is the distance between the front tip of the lens and the mount face.

*3: This circular diaphragm retains a nearly circular shape even when taken at two stops down from its maximum aperture

[C001 Lens Construction] Hybrid Aspherical element LD (Low Dispersion) element AD (Anomalous Dispersion) elements ■ Molded-Glass Aspherical elements

Caution: Please read the instruction manual carefully before using the lens.

C01-FG-121-M-1405-0000



Manufacturer of precise and sophisticated optical products for a broad range of industries

TAMRON CO., LTD.

Diaphragm Blade Number

Minimum Aperture

Compatible Mount

Standard Accessory

1385, Hasunuma, Minuma-ku, Saitama-shi, Saitama 337-8556 JAPAN Tel. +81-48-684-9339 Fax. +81-48-684-9349 http://www.tamron.com

Φ52mm

φ63.5mm

F/22

80 4mm (3 2in)

285g (10.1oz)

Micro Four Thirds

7 (circular diaphragm)*4

Flower-shaped lens hood



Management on Quality and Environment

Tamron is certified with international standards: ISO 9001 for quality and ISO 14001 for environmental management at its headquarters domestic sales offices. China plant as well as three production facilities in Aomori, Japan, and is fully committed to striving for continued and sustainable improvement at all levels and facets of its business operations