



VENUS SERIES

VFLS-1550-B

Features:

- High output power: up to 20W
- Excellent beam quality
- High stability and reliable performance
- All-fiber structure
- Single-mode output

Applications:

- Telecommunication
- Material processing
- Medical procedures
- Test and measurement
- Scientific research

1.5um Single-mode CW Fiber Laser

The 1.5um CW fiber laser of Connet is an eye-safe high power fiber laser. These fiber lasers employ the integrated design of all-fiber structure and use the double cladding fiber pumping technology to realize the high performance output laser. The output power can be up to 20W and the near diffraction-limited beam quality is achieved at the same time. They can be widely used in the areas of scientific research, experimental teaching and device testing.

The 1.5um CW fiber laser of Connet employ the control system based on microprocessor which has stable property, long lifetime and free maintenance. With a clear interface and easy control, the LCD on the front panel can give a real-time display of the operating state of the output power and temperature. The LCD can also offer the warning messages. Besides, in order to be convenient for system integration, our company can offer the modularized package according to the users' requirements.

Specifications:

Parameter	Unit	Specification			
Part No.		VFLS-15-1	VFLS-15-5	VFLS-15-10	VFLS-15-20
Center wavelength	nm	1530~1575			
Output power ¹	W	1	5	10	20
Output power adjustable range	%	10~100			
Spectral width ² (FWHM)	nm	<1			
SMSR	dB	30			
Beam quality	M ²	<1.1			<1.2
Operation mode		CW			
Polarization		Radom (PM optional)			
Output power stability (15mins) ³	%	±0.5			
Output power stability (8h) ³	%	±1			
Output isolation	dB	30			
Return Loss	dB	60			
Operating temperature	℃	0~+50	0~+30		
Storage temperature	℃	-40~+85			
Operating voltage	VAC	100~240			
Output fiber type		SM fiber			LMA fiber
Output fiber length	m	> 1			
Optical connector		FC/APC (other options available)			
Dimension ⁴	mm	19" 2U			19" 3U

Specifications:

- Output power is optional, typical output power: 0.5W、1W、2W、5W、10W;
- Spectral width on request;
- The output power stability is measured under 25℃, after 30 minutes' warm-up;
- Module package is available.

Ordering information:

- VFLS-1550-B-<PW>
- B: Benchtop
- PW: Output power in W, 0.5-0.5W, 2-2W



3/F, Building 322 No.953 Jianchuan Road, Minhang, Shanghai, China

021-61270268

021-61270289

sales@connet-laser.com

www.connet-laser.com



CONNET LASER TECHNOLOGY CO., LTD.