













SECTION A-A

NOTES:

1. Xi = (2i - n - 1) x 0.125, WHERE i CORRESPONDS TO THE 'i'th FIBER PER THE NUMBERING CONVENTION, AND n IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY.
2. MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC #C7438
3. GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6980 TO 0.6990 TO MINIMIZE INSERTION LOSS.

▲ DENOTES CRITICAL DIMENSION

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPRIETARY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: SEE NOTES

REV.	DATE	DESCRIPTION	ECN
X1	1/11/16	---	1795-mm
A	8/4/16	DIM Ø0.126 - 0.127 POS TOL Ø0.003 was Ø0.0026; REVISED TITLE RELEASE	1951-mm
B1	9/27/17	DEL'D FIBER HOLE TRUE POS. SPEC	2048-rr
B	10/20/17	RELEASE	2048-rr

CUSTOMER DRAWING
DIMENSIONS FOR REFERENCE ONLY
THIRD ANGLE PROJECTION
METRIC/mm

USCONEC
Hickory, NC
800-769-0944
www.usconec.com

TITLE
FERRULE, 12F, PPS,
MM MT Elite® W/ DIMPLES

SIZE	S&M Part No.:	DWG NO	REV
B	17184	C17184	B

SCALE	Drafter	Date:	SHEET
N.T.S.	M.McCROSKEY	1/11/2016	1 OF 1