C Lase Optics

Product Specifications 635nm Single Mode Laser



Feature

Description:

- Up to 30mW CW
 out put power
- High Quality, Reliability, & Performance

High brightness, high quality, and high reliability are the foundation of our single mode product line. LaseOptics 635nm multi mode laser diodes are available with up to 30mW of continuous output power from a single emitter chip. LaseOptics trademark laser chip design creates un-measurable degradation and long lifetimes that make our chips among the most reliable in the industry today. Our 635 nm single mode line serves a broad range of applications including solid state pumping, graphics, medical, dental, industrial and defense.

Packaging option include industry standard C-mount, B-mount, and 5.6mm and 9mm. More production options are available upon request.

- Graphics
- Medical/Dental

Applications


- Industrial
- Defense


Contact us today how LaseOptics can help your research and production!

Standard Product Specifications for 635nm Single-mode Diodes

Parameter	Unit	Min.	Тур.	Max.
Wavelength Tolerance	nm	-	3	5
Spectrum FWHM	nm	-	3	5
Operating Voltage (V _o)	V	-	2.4	2.7
Operating Current (Io)	А		90mA	110mA
Life Time	Hours	10,000	-	-
Vertical Far Field	Deg. FWHM	25	30	40
Parallel Far Field	Deg. FWHM	6	7	10
Threshold (Ith)	А	-	50mA	70mA
Slope Efficiency (dP/dl)	W/A	0.8	0.9	-
Storage Temperature	°C	-40	-	85
Operating Temperature (T _{op})	°C	-20	25	40
Lead Soldering Temp. (5sec)	°C	-	-	250

Output Power	Threshold (A)	Operating Current
(W)	Typ./Min	(A) Typ./Max
25 mW	50/60mA	





Note: 1) Specifications are subject to Change without notice.

- 2) All LaseOptics product are TE polarized
- 3) Threshold current varies with chip dimension, most common threshold are given.
- 4) All LaseOptics products are RoHS Compliant

300 International Drive, Amherst, New York, USA-14221 Tel: (716)-462-5078 • **Toll Free: 1-877-420-0021** • Fax: (716)-462-5095 Web: http://www.laseoptics.com • E-mail: info@laseoptics.com LaseOptics: Laser applications in Science & engineering with Optics

Universal Specifications