

Blue Next digital camera LVD-2 (2.3)

The Blue Next digital camera LVD-2 is a HDR-CMOS image sensor camera with LVDS data interface. The camera has a cubic housing layout with HSD connector. Key feature is its very high thermal and mechanical stability. The camera is resistant against harsh environmental conditions like mechanical shocks, vibrations and hazardous atmospheres. Due to its IP6K9K housing the camera is also suitable for outdoor applications.



Features

- LVDS data interface
- 12 VDC
- Low power consumption
- Wide range of fixed focus optics available
- HFoV_{Min}= 52°
- HFoV_{Max}= 192°
- Water tight optic with anti-scratch
- IP6K9K protection class
- Extended operating temperature
- T_{Min}= -40°C
- T_{Max}= +85°C

Applications

- Front view, rear view, area view and blind spot detection
 - Cars
 - Heavy trucks
 - Forklifts
 - Agriculture equipment
 - Mining machines

Certificates

- ISO/TS 16949

Contact

First Sensor Mobility GmbH
Königsbrücker Straße 96
01099 Dresden
Germany
T +49 351 317762-0
F +49 351 317762-12
service@mobility.first-sensor.com

Blue Next digital camera LVD-2 (2.3)

Specifications

Parameter	
Power supply	$V_{DC IN} = 12VDC$
Current consumption	140mA @12VDC and 60 fps
Operating temperature	-40 °C ... +85 °C
Storage temperature	-40 °C ... +85 °C
Water resistance	IPX7, IPX9K (only front side of the camera)
Dust resistance	IP6KX

Technical data

Parameter	Sony imager
Sensor type	1/2.7 inch HDR-CMOS sensor IMX390 WUXGA (1920 x 1200) Full HD (1920x1080)
Sensitivity	Dynamic range: > 100 dB
Data interface	FPD-link III serializer DS90UB953Q 10-100 MHz 10/20-bit DC-balanced Bi-directional (I ² C-controller interface at 400 kHz)
General camera parameter	Automated gain control (AGC) LED Flicker mitigation (LFM) High dynamic range (HDR) Automated white balance (AWB) Shutter: Electronic rolling shutter (ERS)
Optics	52° ±2° horizontal field of view 105° ±2° horizontal field of view 192° ±3° horizontal field of view Anti-reflection coating (ARC), anti-scratch