



The Leader in Small Hole Technology

[Services](#)

[Quality Assurance](#)

[CCI Testing](#)

[Optical Products](#)

[Lenox Orifices](#)

[Clients and Partners](#)

1-800-49-HOLES(46537)

ISO 17025 Certification in Progress

[Home](#) » [Optical Apertures](#) » [Standard Slits](#) » [Cross Aperture](#)



Cross Aperture

\$375.00

1

ADD TO CART

SKU: CROSS-DISC

All products are fully customizable including materials, please [contact us](#) with requests.

Description

Description

The cross aperture may be used * 'for measuring the modulation transfer function (MTF) of a detector array.'

* OPTICAL ENGINEERING / February 1993 / Vol 32 No. 2 / 395

Martin Sensiper, Glenn D. Boreman, Alfred D. Ducharme, and Donald R. Snyder

Specifications

Diameter	50.0 mm ±0.50mm (1.969in ±0.0197in)
Thickness	2.0mm (0.0787in)
Centering	±0.125mm (±0.00492in)
Circularity	< 1.5µ (< 0.000059in)

Aperature Tolerances

Cross Length	25.0 mm
Cross Width	2.0 mm

Orders will be shipped within **5-7 business days** (estimated shipping time not included).

Need Custom Performances?

If a desired product or option(s) is not listed, please contact us for quotes, orders or questions.
(410) 592-3106

Please [Contact Us](#) if you have any questions or to discuss other terms.

Unit Conversion Calculator

Microns
to Inches (i)

Please enter a value to calculate.

[+ Unit Conversion Chart](#)

Lenox Laser, Inc.

12530 Manor Rd.
Glen Arm, MD 21057

1 (800) 49-HOLES (46537)
(410) 592-5300
1 (410) 592-3362 (Fax)



Select Language

Powered by  Google Translate