



8 Center Parkway, Plainfield, CT 06374
1 (860) 963.1141 - 1 (800) 4.SCOPE

High Quality
Professional Scopes



Please Select from the following menu options:

[Expand All](#) | [Collapse All](#)

[Home](#)

[Products](#)

[By Industry](#)

[By Scope](#)

- FSM 10-2 x 36 Fierscope
- IVS 10-4 x 20 Video Scope
- FS 8 x 40 Fiberscope
- FS 6 Fiberscope
- FS 312 Fiberscope
- FS 3 Fiberscope
- FS 120 Fiberscope
- FS 75 Flexible Mining Scope
- FSR 078 Microborescope
- FS 350 Illuminated Viewer
- FS 066 FIBERSCOPE
- IG 350 Flexible viewer
- FSR 039 Microborescope
- VFS 13.7 x 300 cm Fiberscope
- VFS 8-4 x 135 cm Fiberscope
- VFS 6.5-4 x 135 cm Fiberscope
- VFSR 2.0 Fiberscope
- VFS 1.7 Fiberscope

[US Market Price Lists](#)


[Custom Scopes](#)

[Specification Sheets](#)

[Contact Us](#)

FS 066 FLEXIBLE MICROBOSCOPE

The FS 066 was designed to be a portable, rugged inspection device capable of producing a high resolution image of critical components through access holes as small as 1.7 mm. With intense fiber optic illumination and a crisp image delivered by high resolution quartz optical fiber, this microborescope is able to handle a host of inspection requirements where there is limited access.



FS 066 Flexible Microborescope

Standard System Includes:

- High Resolution Fiber Imaging Bundle
- Internal Fiber Optic Illumination
- Portable LED Battery Handle -1 Watt
- Custom Foam Lined Carrying Case
- Durable Steel and Aluminum Construction

Options:

- 150 Watt Illuminator (FO-150)
- Flexible Light Guide
- 35 mm/Digital Still Camera Adapter
- "C" Mount Video Camera Adapter
- "C" Mount Video Camera and Monitor


Shaft O.D.	Shaft Construction	Shaft Lengths	Field of View	Depth of Field	Eyepiece	Direction of View	Light Guide Connector
.066 in. (1.68 mm)	Extruded urethane	6.0 in - (15.2 cm) STD 12.0 in - (30.5 cm) STD	50° STD 70° available	.2 in. to 3.0 in. (5 mm to 75 mm)	B-Style, Diopter Adjustable & Photo Capability	Forward Viewing STD	ACMI



Picture of scope in use



Appropriate picture



Appropriate Picture