

Menu

Home / Imaging / CCD Cameras / VUV EUV X-ray cameras / GE-VUV 1024 256 series /
 GE-VUV 1024 256 FI DD

GE-VUV 1024 256 FI DD



This series of highly sensitive, cooled cameras with vacuum flange is equipped with ultra-low noise 16-bit readout electronics and perfectly suited for spectroscopy and imaging applications in the VUV, EUV and X-ray range up to 20 keV. Due to the large pixel size, very high signal to noise ratios are possible. The CCD detectors deliver spectra and images with outstanding dynamic range. To find the best solution for your application, greateyes offers various flange types and sensor technologies with quantum efficiencies up to 98%.

More Views



Image area	26.6 mm × 6.7 mm
Pixel format	1024 × 256 pixels
Pixel size	26 μm × 26 μm
CCD sensor cooling	Min. -100°C to 20°C, forced air or liquid cooling
Gain	High: 1.0 counts/e- Low: 0.2 counts/e-
Data link	USB, Gigabit Ethernet
Distance flange - focal plane	19.6 mm for CF DN63
Dimensions (H x W x L)	8.7 cm (3.43") x 6.2 cm (2.44") x 12.3 cm (4.84")
Weight (g)	2300
CCD sensor type	Front-illuminated, deep depletion fringe suppression
Full well capacity	700 k e-

Description

Features

Description

This series of highly sensitive, cooled cameras with vacuum flange is equipped with ultra-low noise 16-bit readout electronics and perfectly suited for spectroscopy and imaging applications in the VUV, EUV and X-ray range up to 20 keV. Due to the large pixel size, very high signal to noise ratios are possible. The CCD detectors deliver spectra and images with outstanding dynamic range. To find the best solution for your application, greateyes offers various flange types and sensor technologies with quantum efficiencies up to 98%.

Features

- Sensitive X-ray range: 500 eV to 20 keV
- Up to 85% quantum efficiency
- Front-illuminated CCD, deep depletion CCD

[Request a quote](#)

[Contact](#)

[About Us](#)

[News](#)

© 2018 Laserand, Inc. All Rights Reserved.