


Menu

Home / Imaging / CCD Cameras / VUV EUV X-ray cameras / GE-VUV 2048 512 series / GE-VUV 2048 512 FI

GE-VUV 2048 512 FI



This series of highly sensitive, cooled cameras with vacuum flange is equipped with ultra-low noise 16-bit readout electronics and perfectly suited for spectroscopy and imaging applications in the VUV, EUV and X-ray range up to 20 keV. The CCD detectors deliver spectra and images with outstanding dynamic range. To find the best solution for your application, greateyes offers various flange types and sensor technologies with quantum efficiencies up to 98%.

More Views



Image area	27.6 mm × 6.9 mm
Pixel format	2048 × 512 pixels
Pixel size	13.5 μm × 13.5 μm
CCD sensor cooling	Min. -100°C to 20°C, forced air or liquid cooling
Gain	High: 1.0 counts/e- Low: 0.4 counts/e-
Data link	USB, Gigabit Ethernet
Distance flange - focal plane	19.6 mm for CF DN63
Dimensions (H x W x L)	8.7 cm (3.43") x 6.2 cm (2.44") x 12.3 cm (4.84")
Weight (g)	2300
CCD sensor type	Front-illuminated
Full well capacity	100 k e-

Description

Features

Description

This series of highly sensitive, cooled cameras with vacuum flange is equipped with ultra-low noise 16-bit readout electronics and perfectly suited for spectroscopy and imaging applications in the VUV, EUV and X-ray range up to 20 keV. The CCD detectors deliver spectra and images with outstanding

dynamic range. To find the best solution for your application, greateyes offers various flange types and sensor technologies with quantum efficiencies up to 98%.

Features

- Sensitive X-ray range: 500 eV to 10 keV
- Up to 72% quantum efficiency
- Front-illuminated CCD

[Request a quote](#)

[Contact](#)[About Us](#)[News](#)

© 2018 Laserand, Inc. All Rights Reserved.