

JENOPTIK

High-power single emitter diode lasers: 200 μm , 808 nm, 8 W cw JDL-BAE-33-200-808-TM-8-4.0

Features

- High laser power
- High efficiency
- Long lifetime, high reliability
- Excellent beam characteristics

Applications

- Pumping of solid-state lasers and fiber lasers
- Industrial, scientific and medical systems
- Printing industry
- Defense and security

High-power single emitter diode lasers | 200 μm , 808 nm, 8 W cw

JDL-BAE-33-200-808-TM-8-4.0

Specifications

JDL-BAE-33-200-808-TM-8-4.0

Operation*	Symbol	Min	Nom	Max	Unit
Wavelength (cw)	λ	805	808	811	nm
Optical Output Power	P_{opt}		8		W
Operation Mode			cw, switched		
Power Modulation			100		%
Geometrical					
Number of Emitters			1		
Emitter Width	W	190	200	210	μm
Width	B	580	600	620	μm
Cavity Length	L	3980	4000	4020	μm
Thickness	D	115	120	125	μm
Electro Optical Data*					
Fast Axis Divergence (FWHM)	θ_{\perp}		27	30	$^{\circ}$
Fast Axis Divergence**	θ_{\perp}		46	50	$^{\circ}$
Slow Axis Divergence at 8 W (FWHM)	θ_{\parallel}		7	10	$^{\circ}$
Slow Axis Divergence at 8 W**	θ_{\parallel}		8	11	$^{\circ}$
Pulse Wavelength	λ	800	803	806	nm
Spectral Bandwidth (FWHM)	$\Delta\lambda$		2	3	nm
Slope Efficiency***	η	1.0	1.1		W/A
Threshold Current	I_{th}		1.60	1.80	A
Operating Current	I_{op}		9	10	A
Operating Voltage	V_{op}		1.7	2.0	V
Series Resistance	R_s		17	28	$\text{m}\Omega$
Degree of TM Polarization	α	97			%
EO Conversion Efficiency***	η_{tot}	50	54		%

* Mounted on a heat sink with $R_{th} = 2.1 \text{ K/W}$, coolant temperature $25 \text{ }^{\circ}\text{C}$, operating at nominal power

** Full width at 95 % power content

*** Item may change upon notice and acceptance by JENOPTIK Diode Lab GmbH, due to future improvements of technology or processing

Note:


Nominal data represents typical values.

Safety Advice:


Single emitter diode lasers are the active components in high-power diode lasers in accordance to IEC standard class 4 laser products.

As delivered, single emitter diode lasers cannot emit any laser beam. The laser beam can only be released if the single emitter diode lasers are connected to a source of electrical energy. In this case, IEC-Standard 60825-1 describes the safety regulations to be taken to avoid personal injury.

Power - Current - Voltage - Characteristics*



Spectral Characteristics*



JENOPTIK Diode Lab GmbH | Max-Planck-Strasse 2
12489 Berlin | Germany

Sales contact:

JENOPTIK Laser GmbH
Phone +49 3641 65-3053 | Fax +49 3641 65-4011
laser.sales@jenoptik.com | www.jenoptik.com

