

SIA series underground lights













Features

- ★ Standard DMX512 control protocol
- * Built-in anti-pull connection design for waterproof connector
- ★ High thermal conductivity adhesive, fully potted and waterproof design
- ★ Special protection design for outdoor lightning protection and static electricity (ESD)
- ★ Product flexibility, wide application, multiple installation methods
- ★ Optional anti-glare cover
- ★ Support RGB/W current individually adjustable (low brightness and high gray)

Description

SIA series underground light is a high-power LED underground light product specially designed for outdoor landscape lighting. Adopting high thermal conductivity die-casting aluminum shell, through high thermal conductivity and weather-resistant PU glue potting + sealing ring double waterproof; the appearance of the lamps is exquisite and generous; the lamps are connected through the national standard customized flexible cable, which can be bent or deformed at will; the appearance and color temperature can be customized; Mainly used for decorative lighting and lighting of green belts, parks, lawns, courtyards, streets, parking lots, squares and other places.




Product Size



| Item No. | Diameter | Height | Hole Size | Power |
|----------|----------|--------|-----------|--------|
| S1A120 | Ф 120mm | 90mm | Ф 116mm | 6-12W |
| SIA150 | Ф 150mm | 90mm | Ф 135mm | 9-15W |
| SIA160 | Ф 160mm | 105mm | Ф 145mm | 12-20W |
| SIA180 | Ф 180mm | 105mm | Ф 158mm | 18-27W |
| S1A200 | Ф 200mm | 95mm | Ф 185mm | 24-32W |
| S1A250 | Ф 250mm | 105mm | Ф 236mm | 36-48W |

Installation

Glass glue sealing around the lamp



Sandstone permeable layer

Warning: 1. The connection of lamps and lanterns must be strictly waterproof (above IP67) 2. It is strictly forbidden to soak the lamp in water for a long time, and there must be a permeable layer under the lamp to prevent water accumulation.

Parameters

Color temperature: RGB/W Voltage: DC24V/DC36V Gray level: 256 level / 65536 level Maximum power: 6-48W

LED type: 3030/3535 Work temperature: -20°C to 50°C LED Qty: 6-36pcs Storage temperature: -20°C to 60°C

Shell material: high thermal conductivity aluminum Protection level: IP67 Beam angle: 7°/10°/15°/30°/45°/60° Service life: 50, 000 hours

Model No.

| Item No. | LED Qty | LED Type | Color temperature | Control way | Voltage | Power | Brightness |
|-------------|----------|-----------|-------------------|---------------------|-----------|-------|------------|
| | LLD Qty | | | | | | |
| SIA120-09WN | 6pcs | 3030/3535 | RGB/W | Single color/DMX512 | DC24V/36V | 9W | 630 LM |
| SIA150-12WN | 9pcs | 3030/3535 | RGB/W | Single color/DMX512 | DC24V/36V | 12W | 840 LM |
| SIA160-18WN | 9/12pcs | 3030/3535 | RGB/W | Single color/DMX512 | DC24V/36V | 18W | 1260 LM |
| SIA180-27WN | 12/18pcs | 3030/3535 | RGB/W | Single color/DMX512 | DC24V/36V | 27W | 1890 LM |
| S1A200-36WN | 18/24pcs | 3030/3535 | RGB/W | Single color/DMX512 | DC24V/36V | 36W | 2520 LM |
| SIA250-48WN | 24/36pcs | 3030/3535 | RGB/W | Single color/DMX512 | DC24V/36V | 48W | 3360 LM |