



ИНЖЕКТ^Q

*Menu*Primary Menu

[HOME](#)

[ABOUT US](#)


[PRODUCTS](#)

[NEWS](#)

[FOR SUPPLIERS](#)

[CONTACTS](#)

[RU/EN](#)



multimode fiber

- » Low coherence
- » Built-in photodiode feedback

APPLICATION:

- » Optical fiber gyroscopes and sensors
- » Low Coherence Optical Tomography
- » Optical communication
- » Optical measuring systems

[PREVIOUS PRODUCT](#)

LM4-850B

[NEXT PRODUCT](#)

Emitter of injection lasers IL-1M2

Description

Parameter	Min	normal	max	Units
Radiation power at the output of a fiber optic fiber		8		mW
Length of optical fiber		0.5		m



Инжект[®]

MenuPrimary Menu

[HOME](#)[ABOUT US](#)[PRODUCTS](#)[NEWS](#)[FOR SUPPLIERS](#)[CONTACTS](#)[RU/EN](#)

Diameter of plastic sheath

0.9

μm


Fiber Optic Connector

FC/PC или FC/APC, ST, SC


Operating mode

continuous, pulse

Related products



LM4-850B



LM4-850D



ИНЖЕКТ^Q

*Menu*Primary Menu

[HOME](#)[ABOUT US](#)[PRODUCTS](#)[NEWS](#)[FOR SUPPLIERS](#)[CONTACTS](#)[RU/EN](#)

PRODUCT CATEGORIES

Recruitment gratings of laser diodes for quasi-continuous operation

Semiconductor lasers in pulse mode

Superluminescent diodes

Photodetectors

Other

CONTACTS

410052, Russia, Saratov,

st. Elmashevskaya, 3a

Phone: +7 8452-659707

Fax: +7 8452-437115

E-mail: info@nppinject.ru