

SILICON VALLEY OPTICS TECHNOLOGY

search keyword or Mode

The place where you can always find your best optics fabrication and coating solutions.

- HOME (/)
- PRODUCTS (/all)
- APPLICATION (/all)
- CAPABILITIES
- CORPORATION
- TECHNOLOGY
- CONTACT US (/all) (/contact-us)

Home (/) /All (/all) /Lumicon 2.0" H-BETA

Recently viewed products

Popular tags





Lumicon 2.0" H-BETA

H-BETA

Be the first to review this product (/productreviews/22)

\$205.00

ADD TO CART

[Add to wishlist](#)

[Add to compare list](#)

[Email a friend](#)

0

| | |
|------------------------------|---|
| CWL: | 493.5 +/- 3.0 nm |
| FWHM: | 25.0 +/- 5.0 nm |
| HP: | n/a |
| Transmittance: | 486nm, 496nm & 501nm >= 90% |
| Blocking | T < 0.1% @ 436 nm |
| Blocking | T < 0.01% 440-467 nm |
| Blocking | T < 0.01% 523-630 nm |
| Reflectance (design goal) | |
| 1 of the 2 surfaces | = 1% Max @ 493.5 nm ** |
| Optical Properties: | |
| TWF: | <1.5 Waves, prior to coating |
| Parallelism: | < 30 arcsec. |
| Dimensions: | |
| Diameter: | 2.0 +/- -0.010" |
| Thickness: | 2.0 +/- 0.25 mm |
| Clear Aperture: | 1.95" minimum |
| Cosmetics: | |
| Pinholes: | No pinholes larger than 0.1 mm. Ignore pinholes smaller than 0.025 mm. No more than 5 pinholes between 0.1 and 0.025 mm within any 20 mm diameter area. |
| Surface Quality: | 60-40 Scratch-Dig No Chamfer |
| Operating Conditions: | AOI=0°, Collimated Light |



