

1 to 2 Hz, 2+ mJ, 6 ns


ABOUT L3 KIGRE

L3 Kigre manufactures miniature “eye-safe” diode-pumped 1.54 μm Erbium glass laser transmitters and specialty laser and filter glass materials optimized for use in microchip, microplate, fiber, waveguide and disk laser/ amplifier applications.

PRODUCT OVERVIEW

L3’s MK-82 is an “eye-safe” 1.54 μm diode-pumped passively q-switched Erbium glass laser transmitter with integrated photodiode.

Leaders in Solid State Laser Components



SPECIFICATIONS

Wavelength	1535 nm
Laser Energy	2+ mJ
Pulse Repetition Rate	1 to 2 Hz
Laser Pulse Width	\approx 6 ns
Raw Beam Diameter	0.8 mm
Beam Divergence (D4 σ method)	\leq 4.2 mrad
M ²	\leq 1.7
Beam Wander	\leq 0.5 mrad
Laser Head Size (in inches)	0.65 in. x 1.20 in. x 2.19 in.
Laser Head Size (in centimeters)	1.65 cm x 3.05 cm x 5.56 cm
Laser Head Weight	\approx 136 g
Laser Operational Temperature	-35 °C to +71 °C
Laser Storage Temperature	-55 °C to +90 °C
Electrical Requirements	4 V, 100 A, < 3 ms
Conductive Cooling Requirements	< 2.4 W
Integrated Photodiode?	Yes

L3 Kigre, Inc.

100 Marshland Road
Hilton Head, SC 29926
Tel: 843-681-5800
Fax: 843-681-4559
Email: info.kigre@L3T.com
www.L3T.com/Kigre

This document consists of general capabilities information that is not defined as controlled technical data under ITAR Part 120.10 or EAR Part 772. Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice at L3 Technologies' discretion. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders. Rev 006h

© Copyright 2018 L3 Technologies, Inc., Kigre division. Specifications are approximate and subject to change without notice.