

GenScope, Inc.

18 Deer Park Drive P.O. Box 386 East Longmeadow, MA 01028 (800) 839-9038-tollfree (413) 526-0802-local (413) 526-0809-fax

email:sales@genscope

HOME

PRODUCTS

ABOUT US

CONTACT US

Micro Flex



Micro Semi-Rigid



Micro Rigid




Two-Way Arti-Flex



Heavy-Duty Rigid



Accessories



Micro Rigid GenScopes Ideal for Openings from 1.3mm to 3.0mm

Best for very fine cracks, sharp edges, discolorations, minute defects, or details. Offers straight inline access to the smallest inspection areas.

The GenScope MicroDiameter line of borescopes provides the best image quality in a very smalldiameter borescope -- from 1.3mm to 3.0mm. Typical applications are turbine blades or fuel injectors; micro-rigid borescopes are needed any time a small diameter and quality image is required.



Micro-Diameter Rigid GenScope						
Diameter	Direction Of view	Field of View	Probe Length			D:14 41-
			75mm (2.9")	120mm (4.7°')	165mm (6.5°')	Right Angle Mirror Sleeve
1.3mm	Forward	50	HB1.3-75-F50	HB1.3-120-F50	HB1.3-165-F50	HBA1.3-Length
1.5mm	Forward	50	HB1.5-75-F50	HB1.5-120-F50	HB1.5-165-F50	HBA1.5-Length
2.0mm	Forward	50	HB2.0-75-F50	HB2.0-120-F50	HB2.0-165-F50	HBA2.0-Length
3.0mm	Forward	50	HB3.0-75-F50	HB3.0-120-F50	HB3.0-165-F50	HBA3.0-Length
1.3mm	Right Angle	50	HB1.3-75-R50	HB1.3-120-R50	HB1.3-165-R50	
1.5mm	Right Angle	50	HB1.5-75-R50	HB1.5-120-R50	HB1.5-165-R50	
2.0mm	Right Angle	50	HB2.0-75-R50	HB2.0-120-R50	HB2.0-165-R50	
3.0mm	Right Angle	50	HB3.0-75-R50	HB3.0-120-R50	HB3.0-165-R50	

Site Map