

The NX-Air Series is an upgraded package of the NX that includes an on-board battery that allows for over one hour of untethered operation. The NX-Air can also be configured with an optional WiFi™ module for wireless operation. In this configuration, the camera is fully autonomous and can be operated remotely using a laptop, tablet or Mac iOS device like an iPad®. Power Supply, High G Universal Mounting Plate and Break-out cable for easy out-of-the-box operation are included.



KEY FEATURES

Maximum Resolution	2336 x 1728
Maximum FPS @ Maximum Res	730 fps
Maximum FPS @ Maximum Res (Plus Mode)	1,455 fps
Maximum FPS	110,000 fps @ 2336 x 8
Operating Temperature	-40+50 °C / -40+122 °F

SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	16.4 x 12.1 mm
Sensor Format	1 inch
Pixel Size (micron)	7.00 x 7.00 um
Pixel Depth	10 bit mono 30 bit color
Sensitivity	3000 ISO Mono 1000 ISO Color
Min. Exposure Time	1µs (*Shorter Integration optional)
Array	4.0 megapixel
Quantum Efficiency	50%

MECHANICAL

Weight	0.78 kg or 1.72 lbs
Dimensions	63 x 76 x 97 mm (W x H x L)
Shock & Vibration	Shock: 200G / Vibration: 40G - All axes
Mount	C-Mount standard , F Adaptor optional
IP Rating	0

IMAGE CAPACITY

Image Storage @ Max Frame Rate (DDR 5)	1,005
--	-------

INPUT

Sync-in	Phase-lock TTL
Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
IRIG	Optional (In place of GPS)
GPS Time Code	Standard

OUTPUT

Sync Out	Frame sync / Strobe
----------	---------------------

POWER

Input Voltage	24 VDC
Battery	Operation and battery back-up up to 2 hours

COMMUNICATION

Ethernet	100/1000BaseT
WiFi	Optional
PCie	0

SOFTWARE

Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF

*Integrated Design Tools, Inc. is ITAR compliant. Short Integration rate varies based on camera model.