

NOTES:

1. Material – Base, Carriage: Aluminum
2. Drive: Micrometer – 0.01mm graduation standard
3. Straight Line Accuracy: 0.0005/inch of travel
4. Repeatability: 0.0001
5. Carriage Positional Lock Included




86 Benson Road, Middlebury, CT 06762
 pic-design.com (800) 243-6125
 © 2018 RBC Bearings Inc.

THIS DOCUMENT CONTAINS A GENERAL OVERVIEW OF THE PRODUCTS AND FEATURES DESCRIBED HEREIN. IT IS SOLELY FOR INFORMATIONAL PURPOSES, DOES NOT REPRESENT A WARRANTY OF THE INFORMATION CONTAINED HEREIN, AND IS NOT TO BE CONSTRUED AS AN OFFER TO SELL, OR A SOLICITATION TO BUY. CONTACT PIC DESIGN FOR DETAILED INFORMATION SUITABLE TO YOUR SPECIFIC APPLICATIONS. PIC DESIGN RESERVES THE RIGHT TO MODIFY ITS PRODUCTS AND RELATED PRODUCT INFORMATION AT ANY TIME WITHOUT PRIOR NOTICE. SOME OF THE PRODUCTS LISTED HEREIN MAY BE COVERED BY ONE OR MORE ISSUED AND PENDING U.S. OR FOREIGN PATENTS. CONTACT PIC DESIGN FOR PRODUCT SPECIFIC INFORMATION.

DO NOT SCALE DRAWING
 UNLESS OTHERWISE SPECIFIED,
 TOLERANCES ARE:

INCH	METRIC
XX ± .016	.X ± .8
.XXX ± .005	.XX ± .13
FRACTIONAL ± 1/32	
ANGLES ± 1°	ANGLES ± 1°



UNITS:

Inches

MATERIAL:

Aluminum

HARDNESS:

Unhardened

FINISH:

Anodize

PART NUMBER:

P502MLXYZ

DESCRIPTION:

Positioner : XYZ - Three Axes