

Subnanosecond Actively Q-Switched Solid-State Lasers

PULSELAS®-A Series



A wide range of diode-pumped actively Q-switched lasers with pulse durations around 1 ns are offered by ALPHALAS. They feature high peak powers at various wavelengths in the infrared, visible and ultraviolet as well as excellent TEM₀₀ beam profile.

The PULSELAS®-A series lasers implement proprietary Pockels cell design for generating extremely short laser pulses. The semi-monolithic laser cavity is permanently aligned and therefore extremely stable.

The multi-kilowatt laser pulses can be as short as 500 ps and have a jitter to external signal of typically 500 ps, with option down to 200 ps.

High-energy amplified laser systems (MOPA) deliver more than 1 mJ pulses resulting in the highest peak power >1 MW with pulse widths below 1 nanosecond.

Models with repetition rates from 10 kHz up to 100 kHz and average power ranging from 100 mW to >1 W are available.

The standard models with wavelengths 1047, 1053, 1062 and 1064 nm are complemented by lasers operating at 946 and 1342 nm with pulse durations <5 ns. Optional frequency conversion to red (671 nm), green (532 nm), blue (473 nm) and ultraviolet (355 nm or 266 nm) is also available.

The compact design is perfectly suited for almost any system integration.

These unique lasers have an extremely broad spectrum of applications ranging from supercontinuum generation in photonic crystal fibers to laser-induced breakdown spectroscopy.



Features

- Actively Q-Switched
- Extremely Compact
- Proprietary Electro-Optic Miniature Q-Switch Design
- Subnanosecond Pulses at 1047, 1053, 1062 and 1064 nm
- Extremely Low Jitter (typ. <500 ps, optional 200 ps rms)
- Pulse Energies up to 100 µJ (1 mJ with MOPA)
- Peak Powers up to 150 kW
- Repetition Rates up to 100 kHz
- Average Powers above 1 W
- Frequency Conversion to 266, 355, 473, 532 and 671 nm (Option)

Applications

- Material Processing
- Micromachining
- Marking & Cutting of Extremely Hard Materials (e.g. Diamonds)
- Nonlinear Optics
- Supercontinuum Generation
- Time-Resolved Fluorescence Measurements
- DNA-Analysis
- LIDAR & Laser Ranging
- Pollution Monitoring
- Laser-Induced Breakdown-Spectroscopy (LIBS)
- Ignition of Explosives, Combustion Machines & Gas Mixtures

LASERS, OPTICS, ELECTRONICS.
MADE IN GERMANY.
WWW.ALPHALAS.COM



PULSELAS®-A Series • Actively Q-Switched Lasers @ 1064 nm

| Model | PULSELAS-A-1064-300 | PULSELAS-A-1064-500 | PULSELAS-A-1064-600-HP | PULSELAS-A-1064-1000-HP ¹⁾ |
|--|-------------------------|-------------------------|-------------------------|---------------------------------------|
| Wavelength (nm) | 1064 | 1064 | 1064 | 1064 |
| Energy / Pulse (µJ, typ.) | 20 @ 1 kHz | 40 @ 1 kHz | 50 @ 1 kHz | 100 @ 1 kHz |
| Average Power (mW) @ Max. Rep. Rate | typ. 300 @ 20 kHz | typ. 500 @ 25 kHz | typ. 600 @ 25 kHz | typ. 700 @ 10 kHz |
| Pulse Width (ns) | 0.7 - 1.0 | 1.0 - 1.5 | 1.5 - 2.0 | 1.5 - 3.0 |
| Repetition Rate (kHz) | 0 - 20 | 0 - 25 | 0 - 25 | 0 - 10 |
| Beam Profile | TEM ₀₀ | TEM ₀₀ | TEM ₀₀ | TEM ₀₀ |
| Polarization Ratio | > 100:1 | > 100:1 | > 100:1 | > 100:1 |
| Beam Diameter (mm) | 0.3 | 0.3 | 0.3 | 0.3 |
| Beam Divergence (mrad Full Angle) | typ. 3 | typ. 3 | typ. 3 | typ. 3 |
| Power Instability (% rms, 1 hour) | < 3 | < 3 | < 3 | < 3 |
| Heatsink Operating Temperature (°C) | +18° ... +30° | +18° ... +30° | +18° ... +30° | +18° ... +30° |
| Laser Head Dimensions (W×H×L, mm ³) | 40×52×140 | 40×52×140 | 40×52×140 | 60×70×180 |
| Included LD & TEC Driver (W×H×L, mm ³) | LDD1-1T-D 105×65×100 | LDD1-1T-D 105×65×100 | LDD1-1T-D 105×65×200 | LDD1-1T-F 105×65×200 |
| Pockels Cell Driver (W×H×L, mm ³) | PCD-1002 105×44×100 | PCD-1002 105×44×100 | PCD-1002 105×44×100 | PCD-1002 105×44×100 |
| Operating Temperature (°C) | +18° ... +30° | +18° ... +30° | +18° ... +30° | +18° ... +30° |
| Storage Temperature Without Humidity (°C) | -10° ... +50° | -10° ... +50° | -10° ... +50° | -10° ... +50° |

Notes:

¹⁾ Fiber-pumped laser head.

A built-in frequency generator and external TTL triggering are standard features for all models.

All models are available with options for frequency doubling, tripling and quadrupling to 532, 355 and 266 nm.

Customer specific parameters are available upon request. Please contact us for further information. Specifications for customer specific products are subject to change.



Regulatory Requirements Compliance

The PULSELAS® series diode-pumped solid-state lasers are OEM products intended for integration into other systems. They do not comply with CDRH requirements. The customer is responsible for CDRH certification of the system incorporating the PULSELAS® lasers.

ALPHALAS GMBH
Bertha-von-Suttner-Str. 5
D-37085 Goettingen
Germany

TEL +49 - 551 - 77 06 147
FAX +49 - 551 - 77 06 146
E-MAIL sales@alphalas.com
WEB www.alphalas.com

LASERS, OPTICS, ELECTRONICS.
MADE IN GERMANY.
WWW.ALPHALAS.COM

