

## SB1-946-35-0.1

### Spec. #: SB1-21301

# **Microchip Laser**



### **MAIN FEATURES**

- 946 nm
- < 2 ns</p>
- > 35 uJ
- Single Longitudinal Mode
- All-In-One Miniature Design

Technical Specifications		
Output Wavelength	946	nm
Pulse Repetition Rate	0.1	kHz
Pulse energy	> 35	uJ
Pulse Width	< 2	ns
Peak Power	> 17	kW
Short Term Output Energy Instability (St.Dev. Over > 10000 samples)	< 3 %	
Long Term Output Power Instability (Power log over 24 hours)	< 5 %	
Beam Quality (M²)	< 1.5	
Output Beam Diameter at Exit Aperture (1/e2) without beam expander	< 0.3	mm
Beam Divergence (half angle) without beam expander	< 5	mrad
Beam Ellipticity (axes ratio)	> 0.80	
Warm Up time after cold start	< 5	min
Power Consumption	< 20	W
Mechanical Package	SB1	
Operational Temperature Range	+10°C to +40°C	
Storage Temperature Range	-20°C to +60°C	

All information included in this document are subject to change without notice. Updated data sheets can be provided on request.

For further details, please contact your local **Bright Microlaser** sales representative or visit our website at www.brightmicrolaser.com

**Bright Microlaser Srl** 


Via Artigiani, 21 27010 Cura Carpignano - PV

Italy

**Phone:** +39 0382 583094

e-mail: info@brightmicrolaser.com





### **Options Available:**

- Beam Expander and Collimator
- Heat-sink
- Development kit
- Quick start/evaluation kit

All information included in this document are subject to change without notice. Updated data sheets can be provided on request.

For further details, please contact your local **Bright Microlaser** sales representative or visit our website at www.brightmicrolaser.com

**Bright Microlaser Srl** 

Via Artigiani, 21 27010 Cura Carpignano - PV

Italy

**Phone:** +39 0382 583094

e-mail: info@brightmicrolaser.com