





Trinity COOLED

Thermal Binocular

MAIN SPECIFICATIONS:

 $\begin{tabular}{lll} Spectral Range: & $3 \sim 5 \mu m; \\ Detector: & $320 \times 256 \ InSb/\ MCT \\ Cooler: & Integrating Sterling Cooler \\ \end{tabular}$

Cooling down time:<7.5 Minutes</th>MTBF:>2500 HoursNETD:≤25 mK (detector)

Field Of View: WFOV: 11° ×8. 3° (H×V) +/-10% NFOV: 4° × 3° (H×V) +/-10%

FOV switching time: ≤ 1.5 s, Motorized Focusing: WFOV: $10m \sim \infty$ NFOV: $20m \sim \infty$

Operating Voltage: 24+/-4 VDC; (Option model: 12VDC)
Power Supply: a) Battery (embedded /external)
b) External power supply

Consumption: ≤12 W
Video Format: PAL/NTSC
Video Out: Yes

Detection & Recognition Distance: ≥2.5 Km, against people (0.5m x1.7m)

≥8.0 Km, against vehicle (1.88m (H) x 1.54m (W))

Reticule Display: Yes

Bore Sight Setting: ≤0.1mrad

Battery Capacity: ≥3 hours

Charger Power: 180VAC-250VAC and 24VDC-48VDC

Operating Temperature: $-30^{\circ}\text{C} \sim +55^{\circ}\text{C}$ Storage Temperature: $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$ Weight: $\leq 3.0 \text{ Kg}$ without battery

Sealing: IP65

Eyepiece: Bi-oculars having one objective glass and

one detector system

Mount Interface: 1/4-20

Dimensions (mm): 295 × 245 × 105 mm

Standby Mode: available, switching time less 1 minute

from standby to real time.

Remote Controller: RS422

Hand Held Thermal Imager especially designed for Homeland Security Applications

- Day/Night passive operation
- High Resolution, 800x600 displays
- Image capture/display/reporting
- 3-5µm wavelength

OPTIONAL FUNCTIONS*

- GPS
- VISIBLE LIGHT CCD IMAGE

*Must specify at time of order.

FOR ORDERING: MODEL NUMBER HHTI2500

CANTRONIC SYSTEMS INC.

Cantronic Systems Inc.

(Worldwide Headquarters) 63A Clipper Street

Coquitlam, BC V3K 6X2 Canada Phone: +1.604.516.6667 Toll Free: 1.866.391.6970 Fax: +1.604.516.6618

www.cantronics.com sales@cantronics.com

QWIP Tech. Inc.

(US Subsidiary) 499 Nibus Street Brea, California 92821 Phone: 714.529.7947 Fax: 714.529.7946 www.qwip.com sales@gwip.com

Toll Free: 1.866.391.6970