Data Sheet

28.10.2026

GT 380 Mobile Cable Drum







GT 380			
OUTER HEIGHT	491 mm	**EMPTY WEIGHT**	ca. 3.9 kg
OUTER WIDTH	380 mm	**WEIGHT WITH 240 m CABLE**	ca. 11.9 kg
OUTER DEPTH	291 mm	**MATERIAL**	Plastic
MAX. LENGTH Ø 5 mm	340 m	**MAX. LENGTH Ø 7 mm**	180 m
MAX. LENGTH Ø 6 mm	240 m	**MAX. LENGTH Ø 9.2 mm**	100 m

DESCRIPTION

- High-class portable cable drum
- Robust, suitable for use in harsh environment, e.g. for outdoor applications

Amphenol Sachsenkabel
Address Hauptstraße 110, 09390 Gornsdorf, Germany • **Phone** +49 3721 39 88-0 • **Email** info@sachsenkabel.com
Non-binding data sheet, subject to errors, omissions, and modifications. This document is protected by copyright.

AVAILABLE CONNECTORS			
Eurolens (HMA)	Expanded beam, Amphenol Precision Optics	**MTP®**	US Conec
FO2 / FO4	Fischer Connectors	**3K.93C series**	LEMO
Standard connectors	LC, SC, E-2000® (LSH)	**OTHERS**	on request
AVAILABLE FIBER OPTIC CABLE			
U-DQ(ZN)11Y	Ø 6.5 – 7.7 mm, 12 / 24 fibers	**A-V(ZN)11Y(ZN)11Y**	Ø 6.0 mm, 2 / 4 fibers
OTHERS	on request		
OPTIONAL INTERNAL PATCH PANEL			
SC SIMPLEX ADAPTERS	12 adapters	**LC DUPLEX ADAPTERS**	12 adapters
OTHERS	on request		

OPTIONS

- Also available as stackable version SK 380
- Protection and cable laying tube undetachable
- Auxiliary coil
- Internal patch panel
- Harsh environment connector
- Complete cabling solution with suitable junction boxes

Amphenol Sachsenkabel
Address Hauptstraße 110, 09390 Gornsdorf, Germany • **Phone** +49 3721 39 88-0 • **Email** info@sachsenkabel.com
Non-binding data sheet, subject to errors, omissions, and modifications. This document is protected by copyright.