



Spring Solenoids

DACO offers a full product line of highly reliable and rugged spring solenoids that meet all your application requirements. A wide selection of models, sizes and mounting features are available to match your specific form/fit needs.

[Contact us](#) for more information.

Specifications

DACO's core focus is to provide customized solutions — all built to the most exacting client specifications. Below are sample specifications ranges for models that we manufacture. So if you don't see what you're looking for, [contact us](#) for more information.

| | |
|-------------------|---|
| Diameter | 0.38" to 0.44" |
| Lengths Available | 0.38" to 0.82" |
| Power Input Range | DC – 0.4 to 1.3 watt @ 25°C AC – 0.7 to 1.8 watts @ 25°C |
| Operating Voltage | DC operation: up to 45 volts AC operation: 26 and 115 volts 400Hz |
| Rotation | Up to 60° CW or CCW Standard Tolerance + 3 |
| Shutter Blade | Customized per size/shape and surface finish requirements |



[About Us](#) | [Advanced Laser Shutters](#) | [Rotary Solenoids](#) | [Aircraft Instrumentation](#) | [Contact](#)

Copyright © 2023 Alinabal, Inc. All rights reserved.

[Disclaimer](#) | [Privacy Policy](#) |

Site designed and maintained by [Launch Communications](#).