TECHNICAL SPECIFICATIONS:-

| MODEL | XR - 60 | XR -80 | XR - 100 | XR - 120 | XR - 140 | XR -160 |
|----------------------------------|----------------------------------|----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Input Supply | 415 V AC, 3 Phase, 50Hz | 415 V AC, 3 Phase, 50Hz | 415 V AC, 3 Phase, 50Hz | 415 V AC, 3 Phase, 50Hz | 415 V AC, 3 Phase, 50Hz | 415 V AC, 3 Phase, 50Hz |
| Operating supply voltage range | 370 V AC to 460 AC | 370 V AC to 460 AC | 370 V AC to 460 AC | 370 V AC to 460 AC | 370 V AC to 460 AC | 370 V AC to 460 AC |
| Input power | 10 KVA | 14 KVA | 16 KVA | 21 KVA | 24 KVA | 27 KVA |
| Open Circuit voltage | 320 V DC to 350 V DC | 320 V DC to 350 V DC | 320 V DC to 350 V DC | 320 V DC to 350 V DC | 320 V DC to 350 V DC | 320 V DC to 350 V DC |
| Cutting current range | 20 Amps. DC to 60 Amps. DC | 25 Amps. DC to 80 Amps. DC | 30 Amps. DC to 100 Amps. DC | 40 Amps. DC to 130 Amps. DC | 40 Amps. DC to 140 Amps. DC | 40 Amps. DC to 160 Amps. DC |
| Duty cycle @ 40°C Amb. | 100% at 40 Amps. | 100% at 60 Amps | 100% at 80 Amps. | 100% at 100 Amps. | 100% at 120 Amps. | 100% at 140 Amps. |
| | 80% at 60 Amps. | 80% at 80 Amps. | 80% at 100 Amps. | 80% at 130 Amps. | 80% at 140 Amps. | 80% at 160 Amps. |
| Pilot arc | Electronic Pilot Arc | Electronic Pilot Arc | Electronic Pilot Arc | Electronic Pilot Arc | Electronic Pilot Arc | Electronic Pilot Arc |
| Class of insulation | 'H' Class | 'H' Class | 'H' Class | 'H' Class | 'H' Class | 'H' Class |
| Cooling | Forced air cool | Forced air cool | Forced air cool | Forced air cool | Forced air cool | Forced air cool |
| SS Clean cut | 15 mm | 20 mm | 25 mm | 30 mm | 35 mm | 40 mm |
| Max. Rough cut | 20 mm | 25 mm | 30 mm | 35 mm | 40 mm | 45 mm |
| External Dimension (L.W.H) | 785 mm, 360 mm, 840 mm | 785 mm, 360 mm, 840 mm | 785 mm, 360 mm, 840 mm | 785 mm, 360 mm, 840 mm | 785 mm, 360 mm, 840 mm | 785 mm, 360 mm, 840 mm |
| Gas Supply | Clean, dry, oil free air | Clean, dry, oil free air | Clean, dry, oil free air | Clean, dry, oil free air | Clean, dry, oil free air | Clean, dry, oil free air |
| Weight | 75 Kg. | 75 Kg. | 75 Kg. | 80 Kg. | 85 Kg. | 95 Kg. |
| Flow Pressure | 70 PSI (4.8 bar) @ 11 CFM | 70 PSI (4.8 bar) @ 11 CFM | 70 PSI (4.8 bar) @ 11 CFM | 70 PSI (4.8 bar) @ 11 CFM | 70 PSI (4.8 bar) @ 11 CFM | 70 PSI (4.8 bar) @ 11 CFM |