

Crystal Ovens

Many of widely used nonlinear crystals are susceptible to ambient humidity, for example KD*P, BBO, LBO. Protective coatings applied to the surface can reduce degradation to some extent only. To improve the protection of surfaces of the crystals from the degradation it is desirable to keep the crystals at higher than ambient temperature, which helps avoid condensation on the crystal surfaces.

In addition, if the crystal is used for harmonics generation, the phase-matching angle depends on crystal temperature. For example, the output power of second harmonics generator based on KD*P crystal can decrease by 50 % if the crystal temperature changes just by one degree, hence for good laser stability precise crystal temperature stabilization is necessary.

TEMPERATURE CONTROLLER TC2 WITH OVEN CO1 – TC2 / CO1

TC2 and CO1 is high temperature set (up to 200 °C) consisting of thermocontroller TC2 and crystal oven CO1. TC2 has two independent outputs and can control two CO1-30 ovens simultaneously. Controller is equipped by LAN and USB computer control interfaces.


The nonlinear crystal is mounted into adapter before insertion into oven CO1. Such design facilitates handling and replacement of the crystal. The nonlinear crystal can be sealed with fused silica windows in order to provide extra protection. The standard adapters are 30 and 50 mm length with apertures of 3x3, 4x4, 5x5, 6x6 mm and up to 12x12 mm size. Oven is delivered with one, customer's specific size of adapter. Adapters for different sizes can be ordered separately.



Specifications

MODEL	TC2 + CO1-30	TC2 + CO1-50
Quantity of ovens possible to connect to one controller TC2	2	
Temperature tuning range	RT – 200 °C	
Maximum crystals dimensions	12x12x30 mm	12x12x50 mm
Sealing (optional)	FS windows (operation wavelength must be specified before ordering)	
Temperature tuning step	0.05 °C	
Accuracy	± 0.5 °C	
Long-term stability	± 0.05 °C	
Control interfaces	LAN, USB	
Mains	90–264 V, 47–66 Hz	
Power consumption	< 50 W	
Dimensions, DiaxD	Ø52x52 mm	Ø52x72 mm



Specifications are subject to changes without advance notice.



Temperature controller TC2 outline drawing

Related products

Adapter MS-4 for CO1 mounting on tilt stage



Crystal oven CO1-30 outline drawing